

APPLICANT(S): FEINER, David
SERIAL NO.: 09/982,985
FILED: October 22, 2001
Page 2

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Cancelled)
2. (Cancelled)
3. (Previously Presented) An apparatus comprising:
 - a print head;
 - a movable component attached to a flexible cable carrier, said movable component being coupled to said print head; and
 - an isolating component to isolate uncontrolled movement and vibration of said flexible cable carrier from said at least one print head, wherein said isolating component comprises a linear bearing track attached to a cable carrier support and a generally U-shaped channel attached to said movable component.
4. (Currently Amended) ~~[[An]]~~ The apparatus according to claim 3 comprising:
 - ~~a , wherein said movable component coupled to a print head and having a plate attached at a first end to a flexible cable carrier and~~ comprises a pin attached at a second end of said movable component, said second end being distal from said first end, and wherein a receiver is attached to said print head, said receiver being configured to receive said pin and allow said pin freedom of movement in at least one direction.
5. (Currently Amended) The ~~[[An]]~~ apparatus according to claim ~~[[2]]~~ 3, ~~comprising:~~

APPLICANT(S): FEINER, David
SERIAL NO.: 09/982,985
FILED: October 22, 2001
Page 3

~~a wherein said movable component coupled to a print head and having a plate attached at a first end to a flexible cable carrier and~~ comprises a receiver attached at a ~~second end of said movable component, said second end being distal from said first end,~~ and wherein a pin is attached to said print head, said receiver being configured to receive said pin and allow said pin freedom of movement in at least one direction.

6. (Previously Presented) A method for isolating uncontrolled movement and vibration of a print head from a flexible cable carrier, said method comprising:

attaching a first end of a movable component to said flexible cable carrier;

attaching an isolating component to said movable component;

attaching a pin to a second end of said movable component, said second end being distal from said first end; and

attaching a receiver to said print head, said receiver being configured to receive said pin and allow said pin freedom of movement in one direction.

7. (Previously Presented) The apparatus according to claim 4, wherein said receiver comprises a rubber protector.
8. (Previously Presented) The apparatus according to claim 4, wherein said receiver comprises a silicone protector.
9. (Previously Presented) The apparatus according to claim 5, wherein said receiver comprises a rubber protector.
10. (Previously Presented) The apparatus according to claim 5, wherein said receiver comprises a silicone protector.

APPLICANT(S): FEINER, David
SERIAL NO.: 09/982,985
FILED: October 22, 2001
Page 4

11. (Cancelled)

12. (Cancelled)